



BELSHINA



Robust & Resilient
Off-the-road tyres

OFF-THE-ROAD TYRES RANGE

ROBUST & RESILIENT



BIAS

FT-115

Tyre size	27.00-49
Tyre type	Tubeless (TL)
Tread pattern	Rock
Ply rating	48
Application	Dump truck BelAZ 75-80 tonnage and similar
Rim recommended	19.50-35/4.0
Sectional width, mm	765
Max. load per tyre, index	220
Max load per tyre, kg	25000
Internal pressure, kPa	575
Max. speed, index	B
Max. speed, Km/h	50
Single (O) Dual (S)	O
TKPH	355



BIAS

FT-116AM2

Tyre size	33.00-51
Tyre type	Tubeless (TL)
Tread pattern	Rock
Ply rating	58
Application	Dump truck BelAZ 120-130 tonnage and similar
Rim recommended	24.50-51/5.0
Sectional width, mm	955
Max. load per tyre, index	230
Max load per tyre, kg	35500
Internal pressure, kPa	575
Max. speed, index	B
Max. speed, Km/h	50
Single (O) Dual (S)	O
TKPH	492



BIAS

FT-117

Tyre size	40.00-57
Tyre type	Tubeless (TL)
Tread pattern	Rock
Ply rating	60
Application	Dump truck BelAZ 180-200 tonnage and similar
Rim recommended	29.00-57/6.0
Sectional width, mm	1140
Max. load per tyre, index	244
Max load per tyre, kg	50500
Internal pressure, kPa	500
Max. speed, index	B
Max. speed, Km/h	50
Single (O) Dual (S)	O
TKPH	657



BIAS

Bel-51

Tyre size	21.00-35
Tyre type	Tubeless (TL)
Tread pattern	Rock
Ply rating	36
Application	Dump truck BelAZ 45.4 tonnage and similar
Rim recommended	15.00-35/3.0
Sectional width, mm	572
Max. load per tyre, index	197
Max load per tyre, kg	12850
Internal pressure, kPa	550
Max. speed, index	B
Max. speed, Km/h	50
Single (O) Dual (S)	O
TKPH	

OFF-THE-ROAD TYRES RANGE



BIAS
Bel-76M

Tyre size	18.00-25
Tyre type	Tube type (TT)
Tread pattern	Rock
Ply rating	32
Application	Dump truck BelAZ 30 tonnage and similar
Rim recommended	13.00-25/2.5
Sectional width, mm	498
Max. load per tyre, index	183
Max load per tyre, kg	8750
Internal pressure, kPa	600
Max. speed, index	B
Max. speed, Km/h	50
Single (O) Dual (S)	O
TKPH	



BIAS
Bel-283

Tyre size	35/65-33
Tyre type	Tubeless (TL)
Tread pattern	Rock
Ply rating	30
Application	Buldozers, front loader load capacity 10-20t
Rim recommended	28.00-33/3.5
Sectional width, mm	-
Max. load per tyre, index	214
Max load per tyre, kg	21200
Internal pressure, kPa	425
Max. speed, index	A2
Max. speed, Km/h	10
Single (O) Dual (S)	O
TKPH	



BIAS
Bel-160

Tyre size	46/90-57
Tyre type	Tubeless (TL)
Tread pattern	Rock
Ply rating	68
Application	Dump truck BelAZ 180-200 tonnage and similar
Rim recommended	29.00-57/6.0
Sectional width, mm	1175
Max. load per tyre, index	248
Max load per tyre, kg	56500
Internal pressure, kPa	550
Max. speed, index	B
Max. speed, Km/h	50
Single (O) Dual (S)	O
TKPH	



RADIAL
Bel-162

Tyre size	33.00R51
Tyre type	Tubeless (TL)
Tread pattern	Rock E4
Ply rating	**
Application	Dump truck BelAZ 120-130 tonnage and similar
Rim recommended	24.00-51/5.0
Sectional width, mm	950
Overall diameter, mm	3020
Loaded Static radius, mm	1364
Max. load per tyre, index	236
Max. load per tyre, kg	40100
Internal pressure, kPa	650
Max. speed, index	B
Max. speed, Km/h	50
Single (O) Dual (S)	O
TKPH	

We guarantee high quality of all our products since we have the latest machinery, best experts, we implement the latest achievements of science and technology and entire production cycle is streamlined. Due to their reliability, durability and comfort, tyres from Belshina have gained high reputation with PSU, European and overseas consumers.



OTI INGENIERÍA Y CONSTRUCCIÓN, S.A. DE C.V.

Bld. Benito Juárez No. 505-Altos
Col. Palma, Monclova, Coahuila C.P. 25730
Tel. 01 (866) 633-0510 y 633-3709
Fax 01 (866) 633-1662
info@otiing.com
www.otiing.com